



Ethernet over VDSL2 BNC Cable Converter

UVE7312-MSBC User Manual

Ver 1.02



Table of Content

1. Introductions.....	2
2. Application Notes	2
3. Features	3
4. Packing Contents	3
5. LED Indicators.....	4
6. Dip Switches Settings	4
7. Data Rates & Distances	5

1. Introductions

The UVE7312-MSBC, a VDSL2 (Very high-bit-rate Digital Subscriber Line) Cable Extender, provides a broadband transmission up to 100 / 60Mbps of downstream/upstream data rate over single pair coaxial cable for point-to-point Ethernet connectivity. With 100 / 60Mbps data rate, UVE7312-MSBC supports transmission distance up to 400 meters, and 63 / 27 Mbps for 1.3km long range connection. Users may also select a fixed data rate or a fixed SNR margin for different coaxial cable ranging.

With plug and play features and minimum installation time, each UVE7312-MSBC can be configured into either CO for central side or RT for remote side by dip switch setting. The UVE7312-MSBC conforms to the ITU-T G.993.1 and G.993.2 to meet VDSL / VDSL2 and SG15Q4 DMT for network requirements. A pair of UVE7312-MSBC offers a cost effective solution for bandwidth-hungry applications such as Cable LAN-to-LAN connectivity, Video Streaming, FTTB, and MDU/MTU over single pair coaxial cable.

2. Application Notes

1) Ethernet To Ethernet Bridge Extension over Coaxial Cable



3. Features

- ITU-T G.993.1, G.993.2 VDSL / VDSL2 and SG15Q4 DMT Compliance
- 100 / 60Mbps DownStream / UpStream for distance up to 400 meters
- Supports VDSL2 connection up to 2000 meters
- Line Surge Protection
- BNC Connector for Cable interfaces + RJ45 x 2 for Ethernet LAN port
- Five LED Indicators
- 4 Dip Switches for Configuration Settings
- Trellis Coding support up to 1024 Discrete Multi-Tone (DMT) bins
- Auto MDIX for 10/100 BaseT Ethernet LAN Ports
- Low-Latency for Video / Voice / Data applications
- Selectable Fast and Interleaved modes
 - Fast mode guarantees a minimum end to end latency less than 1 ms.
 - Interleaved mode provides impulse noises protection for any impulse noise with a duration less than 250 us. Interleaved mode has a maximum end to end latency of 10 ms. Interleaved mode is the default mode.
- Selectable fixed data rate and fixed SNR margin
 - User may select fixed SNR margin (9 dB) or fixed target data rate.
 - When fixed SNR margin is selected, the systems will maintain the SNR margin at 9 dB across all available loop length.
 - When fixed target data rate is selected, the system will lock the data rate at 50 / 20Mbps whenever the calculated SNR margin is higher than 9 dB. This will result in the best system stability and is the default mode.

4. Packing Contents

Inside the package you should find:

- (1) One UVE7312-MSBC VDSL2 Cable Extender
- (2) One AC to DC Power Adaptor (5VDC/2A)
- (3) One User Manual CD

Please check if the packing is damaged or any component is missing. If so, please contact your distributor.

5. LED Indicators

On the front panel of UVE7312-MSBC, there are 5 LED indicators as the following

POWER: “Green On” indicates power is on and normal.

LAN1: “Green On” indicates Ethernet LAN1 port is in connection.
“Flashing” indicates Ethernet LAN1 data activities.

LAN2: “Green On” indicates Ethernet LAN2 port is in connection.
“Flashing” indicates Ethernet LAN2 data activities.

BNC: “Green On” indicates VDSL2 Cable is in connection.
“Flashing” indicates VDSL2 Cable is in line handshaking.

M/S: “Green On” indicates UVE7312-MSBC is set as Slave (VTU-R) mode.
“OFF” indicates UVE7312-MSBC is set as Master (VTU-C) mode.

6. Dip Switches Settings



	Pin 1	Pin 2	Pin 3	Pin 4
	VTU-C/R	Mode	Rate Limit	SNR
OFF	VTU-C	Interleaved	50 / 20 Mbps	9dB
ON	VTU-R	Fast	Full Rate	6dB



Pin 1: VTU-C/R Switch

VTU-C: UVE7312-MSBC will act as at the Central Office (CO) side.

VTU-R: UVE7312-MSBC will act as at the Customer Premise Equipment (CPE) or Remote side.



Pin 2: Mode for impulse noise protection

Interleave mode: Protection for up to 250ms impulse noises with latency less than 6 ms.

Fast mode: Direct data transmission with latency less than 1ms.



Pin 3: Rate limit control

50/20 Mbps: Line rate limited to 50 / 20 Mbps.

Full Rate: Provides up to 100Mbps / 60Mbps line rate in short line.



Pin 4: Signal to Noise Ratio (SNR)

9dB: Higher SNR margin (9dB) will result in less error with more stable VDSL2 link.

6dB: Original and Normal channel noise protection with 6 dB SNR.

7. Data Rates & Distances

Performance in 5C2V Cable at 6dB with full rate

Down Stream Data Rate (Mbps)	Up Stream Data Rate (Mbps)	Distance (feet)
107	60	500
103	58	1000
100	56	1250
98	53	1500
96	51	1750
88	48	2000
81	45	2500
77	37	3000
70	32	3500
63	27	4500