



## UKS8102-P2

### 2-Port PS/2 KVM Switch With build-in cables

#### FEATURES

- 2-port all-in-one mini PS/2 KVM switch is compact size design, easy portable
- All-in-one mini PS2 KVM switch built in KVM cable kit, no extra KVM cable needed
- Support Microsoft Intellimouse, Logitech Net Mouse, Microsoft mouse fully compatible mouse, etc.
- Support DOS, Win3.X, Win95 / 98 / 98SE / 2000 / Me / XP / NT, Netware, Unix, Linux
- Connect to USB Macintosh systems or USB SUN Microsystems with optional USB to PS2 converter Y cable
- Hot plug function to add or remove connected PCs for maintenance without powering down the KVM switch or PCs
- Very high video quality up to 2048 x 1536 resolution and 400MHz bandwidth
- No software required for easy PC selection via hot keys
- Auto scan mode for monitoring PCs
- Keyboard status restored when switching PCs
- LED display for easy status monitoring

#### OVERVIEW

The UKS8102-P2 mini PS2 KVM Switch is an electronic switching device for controlling two PCs from one PS/2 Keyboard, one PS/2 Mouse and one VGA Monitor. You don't need to prepare extra cables between PC and console. The KVM switch has complete keyboard and mouse emulation for simultaneous PCs boot-up process. To switch between PCs can be accomplished through keyboard "Hot Key" commands.

The KVM switch provides the best convenience for users who have multiple desktop computers and/or notebooks; or power users who need control multiple servers from one console. It saves your equipment cost, time, space, power, and provides the best convenience of operation.

**SPECIFICATIONS**

System Specifications	
Function	2-Port PS/2 KVM Switch with Cables
PC Port	2
Console Port	1
Audio Port	No
Maximum PC Connections	2
LED Indicators	2
Build-in Cable Length	6 feet (1.8-meter)
PC Port Cable Connector	PS/2 Keyboard (MD6 Male) PS/2 Mouse (MD6 Male) VGA (HD DB15 Male)
Console Port Connector	PS/2 Keyboard (MD6 Female) PS/2 Mouse (MD6 Female) VGA (HD DB15 Female)
PC Selection	Hot Key
Scan Intervals	8 seconds
Keyboard Emulation	PS/2
Mouse Emulation	PS/2
VGA Resolution	2048 x 1536
Bandwidth	400MHz
Power Type	Bus power
Housing	Plastic
Weight	495g
Dimension	80(L) x 60(W) x 26(H) mm (cable not included)
Emission	FCC Class B, CE
Operating Temperature	0 to 50 (32 to 122 )
Storage Temperature	-20 to 60 (-4 to 140 )
Humidity	0% to 90% Non-Condensing

**ORDERING INFORMATIONS**

Model	Description
UKS8102-P2	2-Port PS/2 KVM switch with built-in cables

*EUSSO Technologies, Inc. is a dedicated data communication and networking company. With professional experiences in design, production, marketing and service support, we deliver the full range networking products including Gigabit Ethernet, Fiber Optic, Wireless LAN, Switches, Hubs, LAN cards, PCMCIA adapters, Converter, Transceivers. As well as Internet Telephony Gateway, Print Servers, Internet Sharing Servers and many others.*

UDS8102-P2 v1.0:031218

EUSSO Technologies, Inc.

Tel: +886-2-8221-4616

Email: sales@eusso.com

6F, No.389, Sec.2, Chung Shan Road, Chung Ho City, Taipei 235 Taiwan, R.O.C.

Fax: +886-2-8221-4607

<http://www.eusso.com>